

Light Duty Cable Tray – Pre-Galvanised

Light Duty Perforated Cable Tray | 15 mm Wall | 3 m Length | Pre-Galvanised | 50 – 300 mm

Direct Channel Light Duty Cable Tray is a shallow, perforated tray for supporting lightweight wiring and conduit in commercial and light industrial installations. The 15 mm non-return flange lets lengths slide together with an integrated coupler, while the punched base allows cables to be fixed anywhere along the run.

Roll-formed from steel in standard 3 metre lengths with $\varnothing 8.5 \times 20$ mm slotting; material thickness increases with width (see Available Sizes). Supplied Pre-Galvanised (PG) for internal and moderate-exposure use. Widths from 50 mm to 300 mm.

SPECIFICATION

Product Type	Light duty perforated cable tray
Wall Height	15 mm
Standard Length	3000 mm (3 m)
Flange	Non-return flange, integrated slide coupler
Perforation	$\varnothing 8.5 \times 20$ mm slots
Material Thickness	By width — see Available Sizes
Widths	50 – 300 mm
Finish	Pre-Galvanised (PG)
Compatibility	Couplers (CTL12C.Q2) & variable risers (CTL...-VR)
Supply	Per 3 m length

KEY FEATURES

• 15 mm shallow sidewalls	• $\varnothing 8.5 \times 20$ mm perforation
• Slotted base for cable fixing	• Widths 50 – 300 mm
• Standard 3 m lengths	• Integrated slide coupler
• Pre-Galvanised (PG)	• Lightweight, cost-effective

TECHNICAL DRAWING



Light Duty Cable Tray — cross-section and base detail, dimensions in mm, not to scale

AVAILABLE SIZES

Width (mm)	Thickness (mm)	Code
50	0.8	CTL50
75	0.8	CTL75
100	0.8	CTL100
150	0.9	CTL150
225	0.9	CTL225
300	1.0	CTL300

All lengths 3000 mm (3 m), 15 mm wall height, non-return flange with integrated slide coupler (join with CTL12C.Q2 coupler where required); holes punched at 25 mm centres. Pre-Galvanised (PG) steel. 1 m lengths available to order.

TYPICAL APPLICATIONS

Light wiring & conduit support	Commercial cable containment
Data and comms cabling	Retail & office fit-out
Suspended and wall-mounted runs	General light containment

To Order: Visit directchannel.uk.com or call **0121 270 8507** | Trade & bulk enquiries: sales@directchannel.uk.com | Most orders dispatched same or next working day.

DISCLAIMER & LEGAL NOTICE

Direct Channel Support Systems Ltd has made every reasonable effort to ensure the accuracy and completeness of the information contained in this datasheet. All product specifications, dimensions, and technical details are provided for guidance purposes only. Direct Channel Support Systems Ltd reserves the right to alter, update, or withdraw any product or specification at any time and without prior notice. To the fullest extent permitted by law, Direct Channel Support Systems Ltd accepts no liability for any loss, damage, or consequential loss arising from reliance on the information contained herein. Customers are advised to verify all specifications prior to ordering. For the most current product information visit directchannel.uk.com or contact our sales team.