

Long Spring Channel Nuts - Bright Zinc Plated

Long Spring Channel Nut | Mild Steel | Bright Zinc Plated (BZP) | M6-M12 | Fits 41mm Channel

Direct Channel Long Spring Channel Nuts fit into 41mm strut channel to provide a movable threaded fixing point. The serrated top face engages with the channel return lips and the long spring helps retain the nut in position during installation. Manufactured from steel with a Bright Zinc Plated (BZP) finish for general internal support applications. The long spring holds the nut in position within standard 41mm strut channel while the bolt or fixing is aligned. Supplied in boxes of 100.


SPECIFICATION

Product Type	Spring channel nut (long spring)
Material	Steel
Finish	Bright Zinc Plated (BZP)
Thread	Metric, M6-M12
Length (L)	35mm
Width (W)	19mm
Body Thickness (T)	6-8mm
Spring	Long spring - locates nut in channel
Top Face	Serrated to grip channel lips
Compatibility	Fits standard 41mm strut channel
Use	General strut support fixing
Corrosion	Zinc-plated finish
Supply	Box of 100

KEY FEATURES

• Bright Zinc Plated finish	• Serrated top grips the channel return lips
• Long spring channel nut	• Long spring assists positioning in channel
• Metric thread M6 to M12	• Fits standard 41mm strut channel
• Dimension fields left blank for measurement	• Box of 100

TECHNICAL DRAWING



Long spring channel nut - plan and elevation. Not to scale.

AVAILABLE SIZES

Size	Length (mm)	Width (mm)	Thickness (mm)	Height inc. spring (mm)	Code
M6	35	19	6	45	CNL6
M8	35	19	6	45	CNL8
M10	35	19	7.5-8	47-48	CNL10
M12	35	19	7.5-8	47-48	CNL12

TYPICAL APPLICATIONS

Strut and channel framework fixings	Cable tray and basket support
Pipe and duct support brackets	HVAC and mechanical services
Electrical containment systems	General mounting and bracketry

To Order: Visit directchannel.uk.com or call **0121 270 8507** | Trade & bulk enquiries: sales@directchannel.uk.com | Most orders dispatched same or next working day.

DISCLAIMER & LEGAL NOTICE

Direct Channel Support Systems Ltd has made every reasonable effort to ensure the accuracy and completeness of the information contained in this datasheet. All product specifications, dimensions, and technical details are provided for guidance purposes only. Direct Channel Support Systems Ltd reserves the right to alter, update, or withdraw any product or specification at any time and without prior notice. To the fullest extent permitted by law, Direct Channel Support Systems Ltd accepts no liability for any loss, damage, or consequential loss arising from reliance on the information contained herein. Customers are advised to verify all specifications prior to ordering. For the most current product information visit directchannel.uk.com or contact our sales team.